

SECTION CONTENTS

+7(812)987-08-81



Technical Data.....	204
Parts Information	205
Door Assembly.....	205
Recessed Door Assembly.....	206
Directional Panel Assembly.....	207
Pressure Box Assembly	208
Wiring and Ladder Diagrams	209
208-240V 3PH 50/60 Hz Wiring	209
208-240V 3PH 50/60 Hz Ladder.....	210
440-480V 3PH 50/60 Hz Wiring	211
440-480V 3PH 50/60 Hz Ladder.....	212
380-415V 3PH 50 Hz Wiring	213
380-415V 3PH 50 Hz Ladder	214
208-240V 1PH 50/60 Hz Wiring	215
208-240V 1PH 50/60 Hz Ladder.....	216
Return to Main Table of Contents	3

TECHNICAL DATA


+7(812)987-08-81



7 • 14 Esi SPECIFICATIONS



FRONT VIEW





SIDE VIEW

49-1/8" (1247mm)			TOP VIEW			DIMENSIONS: H x W x D					
INSTALLATION REQUIREMENTS Oven must be installed level. Hood installation is required. Water supply shut-off valve and back-flow preventer.						EXTERIOR: 34-1/4" x 43-7/8" x 42-13/16" (869mm x 1114mm x 1087mm)					
						EXTERIOR WITH RETRACTABLE DOOR: 34-1/4" x 47-7/8" x 42-13/16" (869mm x 1216mm x 1087mm)					
						INTERIOR: 20-5/16" x 23-1/2" x 28-7/16" (515mm x 596mm x 722mm)					
WATER REQUIREMENTS						WATER QUALITY MINIMUM STANDARDS					
TWO (2) COLD WATER INLETS - DRINKING QUALITY						USING A WATER SUPPLY NOT MEETING ALTO-SHAAM'S MINIMUM WATER QUALITY STANDARDS WILL VOID THIS WARRANTY. It is the responsibility of the purchaser to ensure that incoming water supply is compliant with the specifications listed through adequate treatment measures. Installation of the CombiGuard™ Water Filtration System is recommended, but this system may not address all water quality issues present.					
ONE (1) TREATED WATER INLET: 3/4" NPT*											
ONE (1) UNTREATED WATER INLET: 3/4" NPT*											
LINE PRESSURE: 30 to 90 psi 2.8 to 6.2 bar											
WATER DRAIN: 1-1/2" CONNECTION WITH AIR GAP											
* Can manifold off of one 3/4" line.											
CLEARANCE REQUIREMENTS						Contaminant Inlet Water Requirements (untreated water)					
LEFT: 6" (152mm) PLUS SERVICE ACCESS: 18" (457mm) RECOMMENDED 20" (508mm) FROM HEAT PRODUCING EQUIPMENT RIGHT: 4" (102mm) TOP: 20" (508mm) FOR AIR MOVEMENT BACK: 4" (102mm) BOTTOM: 5-1/8" (130mm) FOR LEGS COUNTER-TOP INSTALLATIONS MUST MAINTAIN 4" (102mm) MINIMUM CLEARANCE FROM COUNTER SURFACE.						Free Chlorine Less than 0.1 ppm (mg/L)					
						Hardness Less than 3 gpg (52 ppm)					
						Chloride Less than 30 ppm (mg/L)					
						pH 7.0 to 8.5					
						Alkalinity Less than 50 ppm (mg/L)					
						Silica Less than 12 ppm (mg/L)					
						Total Dissolved Solids (tds) Less than 60 ppm					
ELECTRICAL											
						7•14Esi			7•14Esi/sk		
VOLTAGE		PHASE		CYCLE/HZ		AWG		AMPS		kW	
208-240	at 208	1*		50/60		2 Wire plus ground		67.0		13.9	
	at 240					AWG 3		77.0		18.4	
208-240	at 208	3		50/60		3 Wire plus ground		38.6/ph		13.9	
	at 240					AWG 6		44.3/ph		18.4	
380-415	at 380	3		50/60		4 Wire plus ground		21.1/ph		13.9	
	at 415					AWG 10		25.6/ph		18.4	
440-480	at 440	3*		50/60		3 Wire plus ground		20.0/ph		15.4	
	at 480					AWG 8		22.0/ph		18.4	
* ELECTRICAL SERVICE CHARGE APPLIES											
WEIGHT						CAPACITY					
NET	436 lb	(198 kg)		FULL-SIZE PANS: 20" x 12" x 2-1/2" GN 1/1: 530 x 325 x 65mm GN 2/1: 650 x 530 x 65mm				Fourteen (14) Fourteen (14) Seven (7)		Twelve (12) Twelve (12) Five (5)	
SHIP	560 lb	(254 kg)									
CRATE	42" x 50" x 46" EST.			FULL-SIZE SHEET PANS:* 18" x 26" x 1" ON WIRE SHELVES ONLY				168 lb (76 kg) MAXIMUM			
DIMENSIONS: (1067 x 1270 x 1168mm)											
								VOLUME MAXIMUM: 105 QUARTS (133 LITERS)			

* ADDITIONAL WIRE SHELVES REQUIRED FOR MAXIMUM CAPACITY

ELECTRIC COMBITHERM — INSTALLATION MANUAL #7001




Item	Part	Description	Qty.
1	PI-26973	Pin, Upper	1
2	HG-25078	Hinge, CT, Anchor, ML Combis	2
3	HG-25077	Hinge, CT, Top Stop, ML Combi	1
4	SC-22282	Screw, CT, 1.0X 16 mm, PH Oval, HD N/S 18-8, DIN # 966A	2
5	1005957	Outer Panel, Door	1
6	TA-25125	Tape, Double Sided	2
7	HG-25079	Hinge, CT, Upper Ratchet, Combi	1
8	HD-26966	Handle, Door, Right, Combi '06	1
9	BM-27116	Bumper	2
10	GL-27110	Glass, Outer Door, 7.14 EP	1
11	RI-27108	Rivet, Sealed	22
12	SC-25091	Screw, CT, M5X16, DIN 551, A2 S/S, SLTD Set Screw Flat PT	2
13	BM-27146	Bumper Stop/Inner Door	2
14	SP-27212	Spacer, Window Latch	1
15	SC-27125	Screw, Truss Head, S/S	2
16	PG-24789	Plug, 15 mm	2
17	5005090	Inner Door, Glass Assembly	1
18	PI-26974	Pin, Lower	1
19	5005089	Inner Door Spot RH	1
*	CL-27854	Inner Door Latch	1

*Item Not Shown

PARTS INFORMATION**RECESSED DOOR ASSEMBLY**

7(812)987-08-81



Item	Part	Description	Qty.
1	SC-22924	M6 x 20 Hex Trim HD	2
2	WS-22297	Washer, Flat, M6, DIN 125	14
3	NU-22291	M6-1.0 x Hex S/S Nut 18-8	12
4	WS-22302	Washer, Lock, M6, DIN 127B	12
5	5008015	Right Side Assembly	1
6	5007897	Channel Assembly	1
7	BK-27412	Recessed Door Block	4
8	RA-28207	Rail, Top	1
9	RA-28208	Rail, Bottom	1
10	SC-24388	Screw, SHC M8 x 35 S/S	6
11	5007893	Drip Pan Assembly	1
12	1008869	Cover, Trolley	1
13	5008001	Trolley Assembly	1
14	BK-22100	White Teflon, Cart Guide Block	1
15	1008505	Rear Bracket, Recessed	1
16	SC-22281	Screw, M5 x 16 Flat Head CSink	2
17	BK-28252	Block, Guide	1

Item	Part	Description	Qty.
18	1008506	Front Bracket Recessed	1
19	SC-22284	Screw, M6 x 16 Hex S/S HD	1
20	WS-22298	Washer, M8, 18-8	1
21	HG-28040	Hinge	1
22	HG-25101	Hinge, Lower Ratchet	1
23	5008014	Front Corner Assembly	1
24	SC-26060	M5 x 16 Hex Head	4
25	5008004	Door Assembly Recessed	1
26	WS-25124	Eccesntric Washer	1
27	LG-26867	Legs, Combi	4
28	HG-28041	Hinge	1
29	LT-26968	Latch, Door, Right	1
30	WS-25127	Covering Washer, For Hinge	1
31	PG-25132	M12, (Black or Natural)	1
32	PE-27559	Front Panel Weld Assembly	1
33	5005065	Fill In Cover Assembly	1
34	5007895	Outer Cover Assembly	1


Зип Общепит

vsezip.ru

PARTS INFORMATION

DIRECTIONAL PANEL ASSEMBLY

7(812)987-08-81





Item	Part	Description	Qty.
1	1006361	Directional Panel, 7.14 l	1
2	1006601	Directional Panel Spacer, 16 GA	2
3	WS-24090	Holding (Lock Clip), All Combitherm's ML	2
4	NU-22770	Nut, Threaded Insert, M6	2
5	CL-24089	Clip, CT, ML, Lock, W/3 Washers	2
6	SC-22753	Screw, SS Round, Hanging Rack	2

PARTS INFORMATION

PRESSURE BOX ASSEMBLY

87(812)987-08-81




Item	Part	Description	Qty.
1	5005009	Pressure Box	1
2	EB-25551	Elbow, Nylon, 1/2" x 3/8"	1
3	VA-25549	Valve, 3/8", Flow Control, 0.12 GPM	1

Зип Общепит

vsezip.ru

+7(812)987-08-81




+7(812)987-08-81

MODELS: 714_1010	ESI/ESIN	50°/60Hz
PH:	VOLTS:	WATTS:
1	208-240	14.4-18.5kW
		AMPS: 69.2-79.0A

AUTO-SHAAM

MENDOTA, ILL. U.S.A. 53062-1510

DATE:	DWG:
7/20/07	77035
APP'D:	
BY: MVQ	




NOTES:


N6	DIVEN PROBE	PR-33724
N7	WATER TEMPERATURE PROBE	PR-33759
B3	WATER LEVEL PROBE	PR-3707 (ONLY BOILER)
B5	COOLING WATER PROBE	PR-33751
B4	WATER TEMPERATURE PROBE	PR-33724
B5	STEAM BYPASS PROBE	PR-33751
B11	PRODUCT PROBE	PR-34298
B11	PRODUCT PROBE	PR-33746 (OPTIONAL MULTI-POINT)

Зип Ощепит

vsezip.ru

+7(812)987-08-81










MODEL# 714_1010	ESI/ESIN 50Hz
Part	WATER
3	14.5-18.3kV
	AMP#
	21.6-25.5A



+7(812)987-08-81

MODELS: 714_1010	ESI/ESIN	50/60Hz
PH:	VOLTS:	WATTS:
1	208-240	14.4-18.9kW
		AMPS:
		69.2-79.0A



NOTES:

- 5. DVEN PROBE PR-33724
- 6. WATER TEMPERATURE PROBE PR-33759
- 7. WATER LEVEL PROBE PR-33707 (ONLY BOILER)
- 8. COILING WATER PROBE PR-33751
- 9. WATER TEMPERATURE PROBE PR-33724
- 10. STEAM BYPASS PROBE PR-33751
- 11. PRODUCT PROBE PR-34098
- 12. PRODUCT PROBE PR-33746 (OPTIONAL MULTI-POINT)